## versatile<sup>TM</sup> 4C Mailbox, 4C11D-4P 17" R.O. \_ — 31%," ACTUAL — 30<sup>5</sup>∕′<sub>16</sub>" R.O. — 403/4" 39<sup>13</sup>/<sub>16</sub>" R.O. **ACTUAL** 603/4" (TO PARCEL LOCK) 27/8" FROM 28" FINISHED FLOOR (TO BOTTOM TO BOTTOM OF R.O. SHELF) FINISHED FLOOR COMPARTMENT CHART

## Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
  - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
  - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
  - c. No patron (tenant) lock shall be positioned more than 67" AFF.
  - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
  - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths)  $1\frac{1}{8}$ ".

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX

DESCRIPTION

PARCEL

COMPARTMENT



Address: P.O Box 13144, Wauwatosa, WI 53213
Phone Number: 1-800-676-5161
Website: www.NationalMailboxes.com

	MODEL 4C11D-4P	REV	С
) ).	SCALE NONE	LAS	T REV DATE 5/15/14
er!	DRAWING NUMBER		DRAWN BY
	4C11D-4PCS		RS

COMPARTMENT SIZE

17" H x 12" W x 15" D

20-1/2" H x 12" W x 15" D

QTY.

2