versatile™ 4C Mailbox, 4C11S-04 17" R.O. 17½" ACTUAL |--**DEPTH** - 16¼" R.O. -403/4" 39¹³/₁₆" R.O. 64½" (TO TENANT **ACTUAL** LOCK) 463/4" (TO ACCESS DOOR LOCK) 27/8" FROM 28" FINISHED FLOOR (TO BOTTOM TO BOTTOM OF R.O. SHELF) FINISHED FLOOR COMPARTMENT CHART

Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) $1\frac{1}{8}$ ".

PARCEL PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

DESCRIPTION

MAILBOX

OUTGOING MAIL



COMPARTMENT

OM2

Address: P.O Box 13144, Wauwatosa, WI 53213 Phone Number: 1-800-676-5161 Website: www.NationalMailboxes.com

	MODEL 4C11S-04	REV	D
	scale NONE	LAS	T REV DATE 5/15/14
rt	DRAWING NUMBER		DRAWN BY
	4C11S-04CS		RS

COMPARTMENT SIZE

3" H x 12" W x 15" D

6-1/2" H x 12" W x 15" D

17" H x 12" W x 15" D

4