## versatile™ 4C Mailbox, 4C15S-3P 17" R.O. 17½" ACTUAL |<del>-</del> |**-** 16¼" R.O. **-**543/4" 53<sup>13</sup>/<sub>16</sub>" R.O. ACTUAL 613/4" (TO PARCEL LOCK) 15" $14\frac{1}{8}$ " FROM (TO BOTTOM FINISHED FLOOR SHELF) TO BOTTOM OF R.O. FINISHED FLOOR

## Notes:

- 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
  - a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
  - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
  - c. No patron (tenant) lock shall be positioned more than 67" AFF.
  - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
  - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
- 2. This 4C mailbox can also be used for private applications.
- 3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths)  $1\frac{1}{8}$ ".

## COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
PARCEL	PL5	17" H x 12" W x 15" D	3

PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX



erica's Commercial & Residential Mailbox Leader!

Address: P.O Box 13144, Wauwatosa, WI 53213 Phone Number: 1-800-676-5161 Website: www.NationalMailboxes.com

	MODEL4C15S-3P		REV	D
	SCALE	NONE	LAS	T REV DATE 5/15/14
rt	DRAWING	NUMBER		DRAWN BY
	4C	15S-3PCS		RS